## Detection of multiple articles.

Patent number:

EP0598624

Publication date:

1994-05-25

Inventor:

MARSH MICHAEL JOHN CAMILLE (ZA); LENARCIK ANDRZEJ (ZA); VAN ZYL CLINTON AIDEN (ZA); VAN

SCHALKWYK ANDRIES CHRISTOF (ZA); OOSTHUIZEN MARTHINUS JACOBUS R (ZA)

Applicants

CSIR (ZA); OOSTHUIZEN MARTHINUS JACOBUS R

(ZA)

Classification:

international;

A47F9/04; G01S13/24; G01S13/75; G06K7/00; G06K7/08; G06K7/10; G06K17/00; G07C9/00; G07G1/00; G07G3/00; G08B13/24; H01Q1/22; H01Q21/06; G01S13/87; A47F9/00; G01S13/00; G06K7/00; G06K7/00; G06K7/00; G07G3/00; G08B13/24; H01Q1/22; H01Q21/06; (IPC1-7): G01S13/02;

G01S13/24

- auropean:

A47F9/04D1A; G01S13/24; G01S13/75C8; G06K7/00E;

G06K7/08C6; G06K7/10A2; G06K17/00G; G07C9/00B10; G07G1/00C; G07G1/00C2D;

G07G3/00B; G07G3/00C; G08B13/24B; G08B13/24B6;

H01Q1/22; H01Q21/06B3; H01R1/22

Application number: EP19930309232 19931118
Priority number(s): ZA19920008905 19921118

Also published as:

US5519381 (A1)
JP6223092 (A)
JP2003318776 (A)
BR9304761 (A)
EP0598624 (B1)

more >>

Cited documents:

GB2152335 EP0494114 FR2658059 WO9113415 WO8200910 more >>

Report a data error here

## Abstract of EP0598624

An identification system comprises an interrogator and a plurality of transponders. The interrogator includes a transmitter which transmits at least two independent interrogation signals to the transponders, and a receiver for receiving response signals from the transponders. The interrogator also includes processor means for identifying the transponders from data in the received response signals. Each transponder comprises receiving means, a code generator, and transmitter means connected to the code generator. On receipt of at least one of the transmitted interrogation signals the transponder transmits a response signal containing data which identifies it. The interrogation signals may be transmitted continuously or intermittently. In a preferred embodiment, the interrogation signals are relatively narrow bandwidth signals at different frequencies. The receiving means of each transponder has a relatively broad reception bandwidth so that the transponder is responsive to one or more of the interrogation signals.




Figure 2.